



Slip Less

Floor Cleaner and traction Improver

DESCRIPTION

This is a highly versatile blend of acidic and chelating agents for efficient and safe dissolving of soap scum, minerals, grease and fat from variety of surfaces such as tile and masonry.

Slip Less is being used once a month to shock the quarry tiles in order to provide microscopic traction texture to the tile surface. This method will increase the coefficient of friction of floors, therefore making the floors less slippery and safer work environment.

INSTRUCTIONS

For floor treatment use as is once a month, apply by mop, leave it on the floor for 5-10 minutes then agitate with mop followed by water rinse. This method will increase floor traction in order to achieve less slippery floors.

For daily maintenance, use one ounce per gallon of water and mop the floor.

- **Glazed tiles such as ceramic tile upon treatment with this product will turn to matt finish.**
- **All metals, wood and any other surface should be protected from coming in contact with this product, if it happens need to be rinsed with water immediately.**
- **Highly corrosive to skin and eyes, use rubber gloves and safety glasses when using this product.**

FEATURES

- Increases floor tile traction
- Concentrated for economy

SPECIFICATIONS

Appearance: Clear orange liquid
Odor: Low
Solubility in water: Soluble

pH of 1% solution: 1.5
Detergency: Excellent

Material safety

Contains Ammonium Bifluoride, not safe on metals , glass, painted surfaces.

SAFETY

Keep out of the reach of children! Product is harmful if swallowed. Users should take care to avoid skin contact when using full strength and not allow product to splash into eyes. For skin or eye contact, flush area with clear water for 15 minutes. In the case of eye contact consult physician immediately. Always wash hands completely after use of product.